



# SL800

FICHE TECHNIQUE | DATASHEET

## CARACTERISTIQUES / SPECIFICATIONS

<b>Impression Printing Method</b>	Transfert thermique Thermal Transfer
<b>Résolution</b>	300 DPI
<b>Vitesse d'impression Printing speed</b>	2,3,4 ips
<b>Longueur d'impression Printing Length</b>	Max 1270 mm Max 50 "
<b>Largeur d'impression Printing Wide</b>	Max 219,5 mm 8,64"
<b>Mémoire Memory</b>	8MB Flash Memory 32 MB SDRAM
<b>Interface</b>	RS 232 C Centronics (SPP mode) USB 2.0 client (Full speed) PS/2 Keyboard Interface Internal Ethernet 10/100 print server
<b>Processor</b>	32-bit High performance processor WINDOW DRIVER (WIN 2000/ XP / VISTA / 7)
<b>MEDIA</b>	Rouleaux adhésifs TECHSign SL800 Etiquettes substances chimiques Transfert Thermique Adhesive rolls for SL800 printer Chemical substances labels Thermal ribbon
<b>Dimensions</b>	W 440mm x H 336 mm x D 504 mm
<b>Poids / Weight</b>	23,2 kg
<b>Alimentation Power Source</b>	Internal switching power supply Input : 90-264 VAC, 47-63Hz Output : 24V, 14,5 8A, 350W

